

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL 1311

Revision date: 31.01.2017

Product code: 44

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LASCOL 1311

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cutting oil

1.3. Details of the supplier of the safety data sheet

Company name: LASCOL LUBRIFIANTS
Street: 28 Avenue Carnot, BP 30038
Place: F-78290 CROISSY SUR SEINE
Telephone: +33 09.80.52.18.73
e-mail: lascol.lubrifiants@gmail.com
Telefax: +33 09.57.94.90.76

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-56-9	Baseoil - unspecified, Distillates (petroleum), solvent-dewaxed light paraffinic	15 - < 20 %		
	265-159-2		01-2119480132-48	
	Asp. Tox. 1; H304			
8042-47-5	Weißöle nach dab	15 - < 20 %		
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
93820-57-6	Benzolsulfonsäuren, di-C10-18-alkyl Derivate, Calcium-Salze	1 - < 2.5 %		
	298-637-4			
	Skin Irrit. 2, Aquatic Chronic 3; H315 H412			
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic	0.1 - < 1 %		
	265-156-6		01-2119480375-34	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Seek medical attention if problems persist. No administration in cases of unconsciousness or cramps.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL 1311

Revision date: 31.01.2017

Product code: 44

Page 2 of 6

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. In case of swallowing, keep the patient at rest and contact a doctor.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Extinguishing powder. Carbon dioxide. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

Carbon dioxide (CO₂).

Carbon monoxide

Nitrogen oxides (NO_x).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Large quantities remove mechanically

Clean contaminated articles and floor according to the environmental legislation.

Clean with detergents. Avoid solvent cleaners.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid oil mist

Use only in well-ventilated areas.

Direct contact with skins avoid.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Prevent access by unauthorised personnel.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

LASCOL 1311

Revision date: 31.01.2017

Product code: 44

Page 3 of 6

Further information on handling

High slip hazard because of leaking or spilled product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Recommended storage temperature: 5-40 °C

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Do not store with strong oxidizing agents.

Maximum period of storage (time): 3 Jahre / Years / Jaar

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

Use personal protection equipment as per Directive 89/686/EEC.

Eye/face protection

Use glasses or face shield if there is a risk of splashing.

Hand protection

Protect skin by using skin protective cream. Wear protective gloves if advisable under safety aspects.

Wash hands before breaks and after work.

Gloves of appropriate material (i.e. nitrilic rubber, specification: penetration time: level 6, >480 min., thickness 0,9-1 mm; CE-certified acc. EN 374 cat III)

Skin protection

Chemical resistant safety shoes. Take off immediately all contaminated clothing.

Thorough skin-cleansing after handling the product. Set out skin protection guidelines.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light brown
Odour:	characteristic

pH-Value: not applicable

Changes in the physical state

Initial boiling point and boiling range: >280 °C

Flash point: 165 °C DIN EN 57

Lower explosion limits: 1 vol. %

Upper explosion limits: 10 vol. %

Vapour pressure:
(at 20 °C) 0,05 hPa

Density (at 20 °C): 0,89 g/cm³ EN ISO 12185

Viscosity / kinematic:
(at 40 °C) 23 mm²/s ASTM D 7042

Test method

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL 1311

Revision date: 31.01.2017

Product code: 44

Page 4 of 6

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

Protect against: heat.

10.5. Incompatible materials

The following must be prevented: Oxidizing agents, strong. acid.

10.6. Hazardous decomposition products

Hazardous decomposition products: none

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-56-9	Baseoil - unspecified, Distillates (petroleum), solvent-dewaxed light paraffinic				
	oral	LD50 > 5000 mg/kg	RAT		
	dermal	LD50 >5000 mg/kg	RABBIT		
	inhalative (4 h) aerosol	LC50 >5 mg/l			
8042-47-5	Weißöle nach dab				
	oral	LD50 >5000 mg/kg	Ratte	OECD 401	
	dermal	LD50 >2000 mg/kg	Kaninchen	OECD 402	
	inhalative (4 h) vapour	LC50 >5000 mg/l	Ratte	OECD 403	
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic				
	oral	LD50 >5000 mg/kg	Rabbit		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50 >5 mg/l	Rat		

Additional information on tests

No risks worthy of mention. Practical experience.

The statement is derived from the properties of the single components.

The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
8042-47-5	Weißöle nach dab					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Leuciscus idus	OECD 203	



Safety Data Sheet

according to Regulation (EC) No 1907/2006

LASCOL 1311

Revision date: 31.01.2017

Product code: 44

Page 5 of 6

12.4. Mobility in soil

in delivery condition: liquid

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal number of waste from residues/unused products

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

Other applicable information (land transport)

Not restricted

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

Not restricted

Marine transport (IMDG)

Other applicable information (marine transport)

Not restricted

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

No dangerous good in sense of these transport regulations.

IATA-packing instructions - Passenger:

Not restricted

Other applicable information (air transport)

Not restricted

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Baseoil - unspecified, Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic

2010/75/EU (VOC): <0,1

2004/42/EC (VOC): <0,1

Additional information

According to EC directives or the corresponding national regulations the product does not have to be labelled.

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL 1311

Revision date: 31.01.2017

Product code: 44

Page 6 of 6

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)