# LASCOL ALPHA 76

METALWORKING OIL

UNIVERSAL PROCESSING

(index 2.1)

### MINERAL OIL FREE METALWORKING OIL FOR UNIVERSAL PROCESSING / ALL MATERIALS

### SCOPE

Universal processing on all types of ferrous and non-ferrous materials.

# APPLICATION OF LASCOL ALPHA 76

- Specially developed for cutting operations during thread cutting.
- The product is also suitable for almost all <u>manual</u> metalworking operations, such as drilling, turning, and stamping.
- Suitable for all materials such as steel, non-ferrous metals and aluminium.

## CHARACTERISTICS OF LASCOL ALPHA 76

- Operates extremely economically and offers long tool life and optimum workpiece quality.
- Chlore free.
- Due to the choice of components, it is also very skin-friendly.
- Suitable to minimum quantity lubrication.

#### SKIN FRIENDLY

Kin. viscosity at 40°C: 37 mm²/sec Flash point: >180°C Density at 20 °C : 0.91 g/cm<sup>3</sup>

> Storage temperature: 5 - 40°C Storage time: 36 months

Packaging: 5 I, 10 I and 25 I canisters and 60 I and 209 I drums

LASCOL LUBRIFIANTS BP 30038 78290 CROISSY SUR SEINE, RCS Versailles 508 572 047 00019 TVA intracommunautaire: FR 49 50 85 720 47. Produits fabriqués en Allemagne et distribués en Europe par la Sarl VIP& associés, 28, avenue Carnot -78290 CROISSY SUR SEINE - <u>lascol-lubrifiants.eu</u> lascol.lubrifiants@gmail.com/Téléphone 09 80 52 18 73/Fax 09 57 94 90 76

