

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL ALU PLUS

Revision date: 25.01.2017

Product code: 186

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LASCOL ALU PLUS

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cutting oil

1.3. Details of the supplier of the safety data sheet

Company name:	LASCOL LUBRIFIANTS	
Street:	28 Avenue Carnot, BP 30038	
Place:	F-78290 CROISSY SUR SEINE	
Telephone:	+33 09.80.52.18.73	Telefax: +33 09.57.94.90.76
e-mail:	lascal.lubrifiants@gmail.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

May be fatal if swallowed and enters airways.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

n-Paraffine (C5-C20)

Signal word: Danger**Pictograms:****Hazard statements**

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to hazardous waste.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL ALU PLUS

Revision date: 25.01.2017

Product code: 186

Page 2 of 6

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64771-72-8	n-Paraffine C10-C13			50 - < 100 %
	929-018-5		01-2119475608-26	
	Asp. Tox. 1; H304			
93820-57-6	Benzolsulfonsäuren, di-C10-18-alkyl Derivate, Calcium-Salze			< 0.1 %
	298-637-4			
	Skin Irrit. 2, Aquatic Chronic 3; H315 H412			
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic			< 0.1 %
	265-156-6		01-2119480375-34	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Seek medical attention if problems persist. No administration in cases of unconsciousness or cramps.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. In case of swallowing, keep the patient at rest and contact a doctor.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Extinguishing powder. Carbon dioxide. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

Carbon dioxide (CO₂).

Carbon monoxide

Nitrogen oxides (NO_x).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL ALU PLUS

Revision date: 25.01.2017

Product code: 186

Page 3 of 6

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Large quantities remove mechanically

Clean contaminated articles and floor according to the environmental legislation.

Clean with detergents. Avoid solvent cleaners.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid oil mist

Use only in well-ventilated areas.

Direct contact with skins avoid.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Prevent access by unauthorised personnel.

Further information on handling

High slip hazard because of leaking or spilled product.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Recommended storage temperature: 5-40 °C

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Do not store with strong oxidizing agents.

Maximum period of storage (time): 3 Jahr

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Protective and hygiene measures**

Use personal protection equipment as per Directive 89/686/EEC.

Eye/face protection

Use glasses or face shield if there is a risk of splashing.

Hand protection

Protect skin by using skin protective cream. Wear protective gloves if advisable under safety aspects.

Wash hands before breaks and after work.

Gloves of appropriate material (i.e. nitrilic rubber, specification: penetration time: level 6, >480 min., thickness 0,9-1 mm; CE-certified acc. EN 374 cat III)

Skin protection

Chemical resistant safety shoes. Take off immediately all contaminated clothing.

Thorough skin-cleansing after handling the product. Set out skin protection guidelines.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL ALU PLUS

Revision date: 25.01.2017

Product code: 186

Page 4 of 6

worn.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour: clear
Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Initial boiling point and boiling range: >180 °C
Flash point: 58 °C
Lower explosion limits: 0,5 vol. %
Upper explosion limits: 6 vol. %
Ignition temperature: ca. 200 °C
Vapour pressure: 0,001 hPa
(at 20 °C)
Density (at 20 °C): 0,76 g/cm³ EN ISO 12185
Viscosity / kinematic: 4 mm²/s ASTM D 7042
(at 40 °C)

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

Protect against: heat.

10.5. Incompatible materials

The following must be prevented: Oxidizing agents, strong. acid.

10.6. Hazardous decomposition products

Hazardous decomposition products: none

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64771-72-8	n-Paraffine C10-C13				
	oral	LD50 >5000 mg/kg	rat		
	dermal	LD50 >2000 mg/kg	rbt		
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic				
	oral	LD50 >5000 mg/kg	Rabbit		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50 >5 mg/l	Rat		

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL ALU PLUS

Revision date: 25.01.2017

Product code: 186

Page 5 of 6

Additional information on tests

No risks worthy of mention. Practical experience.

The statement is derived from the properties of the single components.

The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64771-72-8	n-Paraffine C10-C13					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Pimephales Promelas	

12.4. Mobility in soil

in delivery condition: liquid

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste disposal number of waste from residues/unused products**

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)****Other applicable information (land transport)**

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)**Other applicable information (inland waterways transport)**

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)**Other applicable information (marine transport)**

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)**Other applicable information (air transport)**

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL ALU PLUS

Revision date: 25.01.2017

Product code: 186

Page 6 of 6

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)