

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LASCOL CERAM

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.3. Details of the supplier of the safety data sheet**

Company name:	LASCOL LUBRIFIANTS	
Street:	28 Avenue Carnot, BP 30038	
Place:	F-78290 CROISSY SUR SEINE	
Telephone:	+33 09.80.52.18.73	Telefax: +33 09.57.94.90.76
e-mail:	lascol.lubrifiants@gmail.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Keep out of the reach of children.

2.2. Label elements**Regulation (EC) No. 1272/2008**

Signal word: Danger

Pictograms:

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P264	Wash hands thoroughly after handling.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapour/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P312	Call a POISON CENTER/doctor if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if



Safety Data Sheet

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 2 of 8

P304+P340	present and easy to do. Continue rinsing.
P337+P313	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405	If eye irritation persists: Get medical advice/attention.
P403+P233	Store locked up.
P501	Store in a well-ventilated place. Keep container tightly closed.
	Dispose of contents/container to hazardous waste.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Additional advice on labelling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
67-64-1	acetone; propan-2-one; propanone			30-60 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
68476-85-7	Petroleum gases, liquefied; Petroleum gas			10-30%
	270-704-2	649-202-00-6		
	Flam. Gas 1, Carc. 1A, Muta. 1B; H220 H350 H340			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move victim to fresh air. Put victim at rest and keep warm. Do not leave affected person unattended.
Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with: Water and soap. Seek medical attention if problems persist.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Seek medical advice immediately.

After ingestion

Rinse mouth thoroughly with water. Provide fresh air.
Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

refer to chapter 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 3 of 8

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Foam.

Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely. In case of leakage, eliminate all ignition sources.

Additional information

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of fire and/or explosion do not breathe fumes.

Wear personal protection equipment. Keep away from unprotected people. Keep upwind. Provide adequate ventilation. High slip hazard because of leaking or spilled product. Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Provide adequate ventilation. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

In case of leakage, eliminate all ignition sources.

6.4. Reference to other sections

refer to chapter 8

refer to chapter 11

refer to chapter 12

refer to chapter 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Handle and open container with care.

Wash hands thoroughly after handling.

Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

storage temperature: 5 - 40 °C, Do not store at temperatures over: 50 °C

Advice on storage compatibility

Do not store with strong oxidizing agents.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 4 of 8

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
68476-85-7	Liquefied petroleum gas	1000	1750		TWA (8 h)	WEL
		1250	2180		STEL (15 min)	WEL

8.2. Exposure controls**Protective and hygiene measures**

Use personal protection equipment as per Directive 89/686/EEC.

Eye/face protection

Use glasses or face shield if there is a risk of splashing.

Hand protection

Recommended protective gloves brand: none

Skin protection

Chemical resistant safety shoes.

Take off immediately all contaminated clothing.

Thorough skin-cleansing after handling the product.

Respiratory protection

Do not breathe gas/fumes/vapour/spray.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Aerosol
Colour: white
Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: -41 °C

Flash point: -40 °C DIN EN 57

Explosive properties

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material. Danger of bursting container. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits: 1,8 vol. %

Upper explosion limits: 13 vol. %

Ignition temperature: ,

Auto-ignition temperature

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 5 of 8

Solid: 465 °C

Vapour pressure:
(at 20 °C)Density (at 20 °C): 0,76 g/cm³**9.2. Other information****SECTION 10: Stability and reactivity****10.2. Chemical stability**

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Danger of bursting container.

10.5. Incompatible materials

Oxidizing agents.

Further information

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	oral	LD50 mg/kg	5800	Rat	RTECS	
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID	
	inhalative (4 h) vapour	LC50	76 mg/l	Rat		

Sensitising effects

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	6100	48 h Daphnia magna		

12.2. Persistence and degradability

No information available.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 6 of 8

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No information available.

Further information

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of this material and its container to hazardous or special waste collection point.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Limited quantity: LQ2

Other applicable information (land transport)

Special provisions: 190 625
E0
Transport category: 3
Tunnel restriction code: E
Special provisions: 190 - 327 - 625
Transport category: 2
Tunnel restriction code: D

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 7 of 8

14.4. Packing group: -
Hazard label: 2, see SP63

Marine pollutant: •
Limited quantity: See SP277
EmS: F-D, S-U

Other applicable information (marine transport)
Special provisions: 63, 190, 277, 327, 959

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
Hazard label: 2.1



Limited quantity Passenger: -
IATA-packing instructions - Passenger: Forbidden
IATA-max. quantity - Passenger: Forbidden
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)
E0
:-
150 kg

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):
Entry 28: Petroleum gases, liquefied; Petroleum gas
2010/75/EU (VOC): ca. 76% (598 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL CERAM

Revision date: 07.02.2017

Product code: 16800sp1

Page 8 of 8

H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)