

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL DH 600

Revision date: 25.01.2017

Product code: 40

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

LASCOL DH 600

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Cutting oil

1.3. Details of the supplier of the safety data sheet

Company name:	LASCOL LUBRIFIANTS	
Street:	28 Avenue Carnot, BP 30038	
Place:	F-78290 CROISSY SUR SEINE	
Telephone:	+33 09.80.52.18.73	Telefax: +33 09.57.94.90.76
e-mail:	lascol.lubrifiants@gmail.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Reproductive toxicity: Lact.

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

May cause harm to breast-fed children.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

alkanes, C14-17, chloro; chlorinated paraffins, C14-17

Pictograms:**Hazard statements**

H362	May cause harm to breast-fed children.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P263	Avoid contact during pregnancy and while nursing.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous waste.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL DH 600

Revision date: 25.01.2017

Product code: 40

Page 2 of 7

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17			15 - < 20 %
	287-477-0	602-095-00-X		
	Lact., Aquatic Acute 1, Aquatic Chronic 1; H362 H400 H410 EUH066			
4259-15-8	2-Ethylhexyl-zink-dithiophosphat			1 - < 2.5 %
	224-235-5		01-2119493635-27	
	Aquatic Chronic 2; H411			
93820-57-6	Benzolsulfonsäuren, di-C10-18-alkyl Derivate, Calcium-Salze			0.1 - < 1 %
	298-637-4			
	Skin Irrit. 2, Aquatic Chronic 3; H315 H412			
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic			0.1 - < 1 %
	265-156-6		01-2119480375-34	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Seek medical attention if problems persist. No administration in cases of unconsciousness or cramps.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. In case of swallowing, keep the patient at rest and contact a doctor.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Extinguishing powder. Carbon dioxide. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

Carbon dioxide (CO₂).

Carbon monoxide

Nitrogen oxides (NO_x).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

LASCOL DH 600

Revision date: 25.01.2017

Product code: 40

Page 3 of 7

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Large quantities remove mechanically

Clean contaminated articles and floor according to the environmental legislation.

Clean with detergents. Avoid solvent cleaners.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid oil mist

Use only in well-ventilated areas.

Direct contact with skins avoid.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Prevent access by unauthorised personnel.

Further information on handling

High slip hazard because of leaking or spilled product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Recommended storage temperature: 5-40 °C

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Do not store with strong oxidizing agents.

Maximum period of storage (time): 3 Jahr

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

Use personal protection equipment as per Directive 89/686/EEC.

Eye/face protection

Use glasses or face shield if there is a risk of splashing.

Hand protection

Protect skin by using skin protective cream. Wear protective gloves if advisable under safety aspects.

Wash hands before breaks and after work.

Gloves of appropriate material (i.e. nitrilic rubber, specification: penetration time: level 6, >480 min., thickness 0,9-1 mm; CE-certified acc. EN 374 cat III)

Skin protection

Chemical resistant safety shoes. Take off immediately all contaminated clothing.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL DH 600

Revision date: 25.01.2017

Product code: 40

Page 4 of 7

Thorough skin-cleansing after handling the product. Set out skin protection guidelines.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour: dark brown
Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Initial boiling point and boiling range: not determined

Flash point: >180 °C DIN EN 57

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 6,5 vol. %

Vapour pressure: not determined

Density (at 20 °C): 0,94 g/cm³ EN ISO 12185Viscosity / kinematic:
(at 40 °C) 34 mm²/s ASTM D 7042**SECTION 10: Stability and reactivity****10.4. Conditions to avoid**

Protect against: heat.

10.5. Incompatible materials

The following must be prevented: Oxidizing agents, strong. acid.

10.6. Hazardous decomposition products

Hazardous decomposition products: none

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
4259-15-8	2-Ethylhexyl-zink-dithiophosphat				
	oral	LD50 mg/kg	4358	Ratte	
64742-53-6	Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic				
	oral	LD50 mg/kg	>5000	Rabbit	
	dermal	LD50 mg/kg	>5000	Rabbit	
	inhalative (4 h) vapour	LC50	>5 mg/l	Rat	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL DH 600

Revision date: 25.01.2017

Product code: 40

Page 5 of 7

Additional information on tests

No risks worthy of mention. Practical experience.

The statement is derived from the properties of the single components.

The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information**12.4. Mobility in soil**

in delivery condition: liquid

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste disposal number of waste from residues/unused products**

120106 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils containing halogens (except emulsions and solutions); hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

UN3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
alkanes, C14-17, chloro; chlorinated paraffins, C14-17**14.3. Transport hazard class(es):**

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 601

Limited quantity:

5 L

Transport category:

3

Hazard No:

90

Other applicable information (land transport)

E1

Inland waterways transport (ADN)**14.1. UN number:**

UN3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 601

Limited quantity:

5 L

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL DH 600

Revision date: 25.01.2017

Product code: 40

Page 6 of 7

Other applicable information (inland waterways transport)

E1

Marine transport (IMDG)

14.1. UN number: UN3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Special Provisions: 274, 335
Limited quantity: 5 L
EmS: F-A, S-F

Other applicable information (marine transport)

E1

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Special Provisions: A97 A158
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

E1

: Y964

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic

National regulatory information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

LASCOL DH 600

Revision date: 25.01.2017

Product code: 40

Page 7 of 7

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - clearly water contaminating

SECTION 16: Other information**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Lact.; H362	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H362 May cause harm to breast-fed children.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)