



LASCOL

GEL DE MAINTENANCE

CUTTING GEL

(index 4.2)

CUTTING GEL FOR SEVERE MACHINING

**MICRO
APPLICATION**

SCOPE

- The LASCOL GEL DE MAINTENANCE has been formulated to give excellent results on all types of ferrous or non-ferrous materials.
- micro application/portable use.

APPLICATION OF LASCOL GEL DE MAINTENANCE

- Specially developed for very heavy machining operations such as threading, drilling, milling...of alloyed and unalloyed steel as well as chrome-nickel steel, titanium, manganese carbon steel, cast iron, cast steel, malleable iron.
- For materials like steel, aluminium, copper, castings, zinc and its alloys.
- Allows long tool life and very good surface quality of the material to be machined.

CHARACTERISTICS OF LASCOL GEL DE MAINTENANCE

- Economical in use due to targeted application **at the spot** to be machined.
- Due to the gel-like consistency, the LASCOL GEL DE MAINTENANCE can be used wherever a paste or oil does not achieve the desired result due to viscosity
- Due to small size of the package, the gel will fit into any pocket and ideal for the portable use

VERY PRECISE APPLICATION

Kin. viscosity at 40°C: -
Flash point: 270°C Density at 20 °C : 1 g/cm³

Storage temperature: 5 - 40°C
Storage time: 36 months

Packaging: 120 g tube